

**Basic specification:**

- ✓ Disk brakes
- ✓ Hopper with a capacity of 3,0 m<sup>3</sup>
- ✓ Safety grid in the hopper
- ✓ Auger from wear resistant steel
- ✓ Bag lifting device
- ✓ Winch for operating bag pan
- ✓ Wheels: 400/60R15
- ✓ Tunnel 9 feet (2,7 m)
- ✓ Hitch 40 mm on tractor drawbar
- ✓ Adjustable height drawbar

**Optional:**

- ✓ Tunnel 10 feet (3 m)
- ✓ Applicator with barrel holder and nozzles
- ✓ Maxamon-applikator
- ✓ Hopper extension to 3,5 m
- ✓ Hitch ball K-80 on tractor drawbar

**Specifications:**

PTO speed	rpm	540
Tractor power	hp	100-160
Performance machine	ton/h	180-250

**Dimensions of the machine:**

Length	mm	5.210
Width	mm	3.405
Height	mm	2.705
Machine weight	kg	2.000



**GS BAGGER D9**

Low built, reliable, high capacity universal grain bagger for all sorts of grain with bagging capacity exceeding 250 ton/h



Per Christerson  
Tel. +46-70-3216262  
per@farmmac.com

Krister Wiengren  
Tel. +46-73-3335130  
krister@farmmac.com

DISCLAIMER: Grain Saver is continually being further developed. We reserve the right to change specifications, prices and models at any time. Illustrations and specifications are approximately binding.